

CAS

Type	D42	D52	D62	DE42
Pitch	7.0mm	7.0mm	7.0mm	7.5mm
Number of shuttles	420	520	620	420
Spool diameter	180mm	180mm	180mm	180mm
Applicable twine				
Nylon multi.	122T/2 – 235T/9 (110d/2 – 210d/9)	122T/2 – 235T/9 (110d/2 – 210d/9)	122T/2 – 235T/9 (110d/2 – 210d/9)	122T/2 – 235T/15 (110d/2 – 210d/15)
Polyethylene	250d/2 – 380d/4	250d/2 – 380d/4	250d/2 – 380d/4	250d/3 – 380d/6
Mesh range (in stretch)	11 – 320mm	11 – 320mm	11 – 320mm	12 – 320mm
Production speed	Up to 30 r.p.m.	Up to 28 r.p.m.	Up to 26 r.p.m.	Up to 30 r.p.m.

Type	DE43	DE52	DE53	DE62
Pitch	7.5mm	7.5mm	7.5mm	7.5mm
Number of shuttles	430	520	530	620
Spool diameter	180mm	180mm	180mm	180mm
Applicable twine				
Nylon multi.	122T/2 – 235T/15 (110d/2 – 210d/15)	122T/2 – 235T/15 (110d/2 – 210d/15)	122T/2 – 235T/15 (110d/2 – 210d/15)	122T/2 – 235T/15 (110d/2 – 210d/15)
Polyethylene	250d/3 – 380d/6	250d/3 – 380d/6	250d/3 – 380d/6	250d/3 – 380d/6
Mesh range (in stretch)	12 – 320mm	12 – 320mm	12 – 320mm	12 – 320mm
Production speed	Up to 30 r.p.m.	Up to 28 r.p.m.	Up to 28 r.p.m.	Up to 24 r.p.m.

Type	DE64	H52		
Pitch	7.5mm	9.0mm		
Number of shuttles	640	520		
Spool diameter	180mm	200mm		
Applicable twine				
Nylon multi.	122T/2 – 235T/15 (110d/2 – 210d/15)	235T/3 – 235T/21 (210d/3 – 210d/21)		
Polyethylene	250d/3 – 380d/6	380d/3 – 380d/9		
Mesh range (in stretch)	12 – 320mm	16 – 320mm		
Production speed	Up to 24 r.p.m.	Up to 24 r.p.m.		