

# LAS

Type	D65	DE62	E54	H52
Pitch	7.0mm	7.5mm	8.0mm	9.0mm
Number of shuttles	650	620	540	520
Spool diameter	210mm	210mm	210mm	230mm
Applicable twine				
Nylon multi.	122T/2 – 235T/9 (110d/2 – 210d/9)	122T/2 – 235T/12 (110d/2 – 210d/12)	235T/3 – 235T/18 (210d/3 – 210d/18)	235T/3 – 235T/21 (210d/3 – 210d/21)
Polyethylene	250d/2 – 380d/4	250d/2 – 380d/6	380d/2 – 380d/9	380d/3 – 380d/12
Mesh range (in stretch)	11 – 400mm	12 – 400mm	12.5 – 400mm	12.7 – 400mm
Production speed	Up to 23 r.p.m.	Up to 23 r.p.m.	Up to 24 r.p.m.	Up to 24 r.p.m.

Type	I42	J42	K42	L36
Pitch	3/8" (9.5mm)	13/32" (10.3mm)	7/16" (11.1mm)	1/2" (12.7mm)
Number of shuttles	420	420	420	365
Spool diameter	250mm	250mm	250mm	250mm
Applicable twine				
Nylon multi.	235T/3 – 235T/30 (210d/3 – 210d/30)	235T/3 – 235T/36 (210d/3 – 210d/36)	235T/3 – 235T/36 (210d/3 – 210d/36)	235T/6 – 235T/48 (210d/6 – 210d/48)
Polyethylene	380d/3 – 380d/12	380d/3 – 380d/15	380d/3 – 380d/15	380d/4 – 380d/21
Mesh range (in stretch)	13 – 400mm	14.6 – 400mm	16.4 – 400mm	18 – 400mm
Production speed	Up to 25 r.p.m.	Up to 25 r.p.m.	Up to 24 r.p.m.	Up to 22 r.p.m.

Type	M32	NO26	P21	
Pitch	9/16" (14.2mm)	11/16" (17.4mm)	7/8" (22.2mm)	
Number of shuttles	320	260	210	
Spool diameter	250mm	250mm	250mm	
Applicable twine				
Nylon multi.	235T/9 – 235T/60 (210d/9 – 210d/60)	235T/12 – 235T/90 (210d/12 – 210d/90)	235T/15 – 235T/120 (210d/15 – 210d/120)	
Polyethylene	380d/6 – 380d/30	380d/9 – 380d/45	380d/12 – 380d/60	
Mesh range (in stretch)	20 – 400mm	28 – 400mm	33 – 400mm	
Production speed	Up to 23 r.p.m.	Up to 22 r.p.m.	Up to 21 r.p.m.	

Model LAS Specification