

NXS

Type	H66	I63	K54	L47
Pitch	9.0mm	3/8"(9.513mm)	7/16"(11.0985mm)	1/2"(12.7mm)
Number of shuttles	660	630	540	470
Spool diameter	250mm	250mm	250mm	250mm
Applicable twine				
Nylon multi.	235T/3 – 235T/21 (210d/3 – 210d/21)	235T/3 – 235T/30 (210d/3 – 210d/30)	235T/3 – 235T/36 (210d/3 – 210d/36)	235T/15 – 235T/48 (210d/15 – 210d/48)
Polyethylene	420T/3 – 420T/12 (380d/3 – 380d/12)	420T/3 – 420T/12 (380d/3 – 380d/12)	420T/3 – 420T/15 (380d/3 – 380d/15)	420T/9 – 420T/21 (380d/9 – 380d/21)
Mesh range (in stretch)	15 – 600mm	15 – 600mm	19 – 600mm	22 – 600mm
Production speed	Up to 16 r.p.m.	Up to 16 r.p.m.	Up to 16 r.p.m.	Up to 16 r.p.m.

Type	M44	N37	NO34	O31
Pitch	9/16"(14.2695mm)	5/8"(15.855mm)	11/16"(17.4405mm)	3/4"(19.05mm)
Number of shuttles	440	370	340	310
Spool diameter	300mm	300mm	300mm	300mm
Applicable twine				
Nylon multi.	235T/12 – 235T/54 (210d/12 – 210d/54)	235T/21 – 235T/75 (210d/21 – 210d/75)	235T/21 – 235T/75 (210d/21 – 210d/75)	235T/24 – 235T/105 (210d/24 – 210d/105)
Polyethylene	420T/9 – 420T/27 (380d/9 – 380d/27)	420T/12 – 420T/36 (380d/12 – 380d/36)	420T/12 – 420T/36 (380d/12 – 380d/36)	420T/15 – 420T/48 (380d/15 – 380d/48)
Mesh range (in stretch)	25 – 600mm	28 – 600mm	30 – 600mm	32 – 600mm
Production speed	Up to 14 r.p.m.	Up to 13 r.p.m.	Up to 13 r.p.m.	Up to 13 r.p.m.

Type	P27	Q21		
Pitch	7/8"(22.225mm)	1"(25.4mm)		
Number of shuttles	270	210		
Spool diameter	300mm	300mm		
Applicable twine				
Nylon multi.	235T/24 – 235T/150 (210d/24 – 210d/150)	235T/27 – 235T/180 (210d/27 – 210d/180)		
Polyethylene	420T/15 – 420T/66 (380d/15 – 380d/66)	420T/18 – 420T/84 (380d/18 – 380d/84)		
Mesh range (in stretch)	36 – 600mm	44 – 600mm		
Production speed	Up to 13 r.p.m.	Up to 14 r.p.m.		

Model NXS Specification